




PERFORMANCE

TEMPERATURE RANGE	-30°C / +18°C
HUMIDITY RANGE	40% / 90%
STEP GASTRONOMY GUIDES	60 mm
PASTRY SET-UP	Pairs of "L" guides
STEP PASTRY GUIDES	60 mm

CHECK



FEATURES

- AISI 304 stainless steel construction with external scotch brite finish
- Monocoque structure with increased loading volume
- Foamed engine compartment sides for improved strength and soundproofing
- Rounded edges interior to facilitate cleaning
- Self-closing and reversible doors (with kit)
- Door frame with removable heating element
- Door gasket easy to remove without dedicate working tools
- Feet in stainless steel adjustable in height
- Possibility of inserting up to 36 shelves with a 35mm pitch
- Refrigerant gas R290
- Static refrigeration system
-
- Internet ready/cloud/diagnosis and remote control
- Multi-phase leavening, programmable
- Possibility to memorize recipes

DIMENSIONS

Width	790 mm [31.1 in]
Depth	1030 mm [40.55 in]
Height	2110 mm [83.07 in]
Weight	160 kg [352.8 lb]
Foot height	97-159 mm [3.82-6.26 in]
Door light width 1	620 mm [24.41 in]
Door light height 1	1510 mm [59.45 in]
Door depth open 90°	1760 mm [69.29 in]
Internal depth	820 mm [32.28 in]
Packaging width	845 mm [33.27 in]
Packing depth	1095 mm [43.11 in]
Packaging height	2200 mm [86.61 in]
Packing weight	195 kg [429.98 lb]
Packing volume	2.03 m ³ [537.75 glus]

TECHNICAL DATA

Temperature range	-30°C / +18°C
Humidity range	40% / 90%
Insulation thickness	85 mm [3.35in]
Number of rooms	1
Door type	Blind
Number of doors	1
Compressor type	Hermetic
Refrigerant gas	R290
GWP refrigerant gas	3
Refrigerant gas quantity g	150 g [9.38oz]
Sound power	<70 dbA
Defrost type	Hot Gas
Cooling power	594 W
Climatic class	5
Energy class	C
lee	36.5
kW/24h	6.36 kW

CAPABILITIES

GN grids	[]
GN guides step	60 mm
EN Setup	Pairs of "L" guides
EN Guides	24
EN Grids	[]
Step guides EN	60 mm

CAPABILITIES

IC grids	□
----------	---

SUPPLY

Power supply	220-240 V ~ 50 Hz
FLI - Max cold power	1250 W
FLA - Max cold absorption	5.3 A
Power cable	(2+1) x 1,5 mm ²
Power plug	CE-Schuko