




PERFORMANCE

PRODUCT YIELDS +90°C/+3°C	60 kg
PRODUCT YIELDS +90°C/-18°C	40 kg
TEMPERATURE RANGE	-40°C / +5°C
CAPABILITIES	15 pans
STEP GASTRONOMY GUIDES	68 mm
STEP PASTRY GUIDES	17.5 mm
STEP ICE CREAM GUIDES	17.5 mm
ICE CREAM TRAYS 165x360x120h mm	21
ICE CREAM TRAYS 250x360x120h mm	14
ICE CREAM TRAYS 250x360x120h mm	12

CHECK



FEATURES

- Latest generation fans
- Insulation in high density expanded polyurethane (approximately 42 kg/m3), HCFC free - Thickness 60 mm
- Core probe
- Total inspectability of the room for maximum hygiene
- Condensate collection tray
- Air condensation
- Heated core probe included
- Refrigerant fluid R290
- Evaporating coil in copper-aluminum, cataphoresis painted with non-toxic epoxy resin
- 2.8" LCD graphic display and capacitive keys
- IPX4 organized electrical panel on the front, easy to access

OPTIONAL

- Water condensing unit
- Wheel kit
- 4.0 bi-directional connectivity and Wi-Fi

STANDARD EQUIPMENT

AISI 304 stainless steel supports for GN1/1 or 600x400 trays

OPTIONAL EQUIPMENT

Internal structure with variable pitch featuring 15 pairs of removable "L" guides in AISI 304 stainless steel, positionable to fit every 17.5 mm

Internal structure with variable pitch featuring 15 pairs of removable anti-tipping "C" guides in AISI 304 stainless steel, positionable to fit every 17.5 mm

DIMENSIONS

Width	790 mm [31.1 in]
Depth	900 mm [35.43 in]
Height	1880 mm [74.02 in]
Weight	190 kg [418.95 lb]
Foot height	145-205 mm [5.71-8.07 in]
Door light width 1	670 mm [26.38 in]
Door light height 1	1130 mm [44.49 in]
Door depth open 90°	1530 mm [60.24 in]
Internal depth	410 mm [16.14 in]
Packaging width	850 mm [33.46 in]
Packing depth	950 mm [37.4 in]
Packaging height	2045 mm [80.51 in]
Packing weight	196 kg [432.18 lb]
Packing volume	1.65 m ³ [436.23 glus]

TECHNICAL DATA

Temperature range	-40°C / +5°C
Insulation thickness	60 mm [2.36in]
Number of rooms	1
Door type	Blind
Number of doors	1
Condensation type	Air
Plant type	Motor on board
Plant type	Ventilated
Compressor type	Hermetic
Refrigerant gas	R290
GWP refrigerant gas	3
Refrigerant gas quantity g	2 x 150 g [2 x 5.91oz]
Sound power	<70 dbA
Expansion valve type	Mechanics
Defrost type	Open door
Defrost water evaporation	Automatic
Interior lighting	Not present
Cooling power	7659 W
Climatic class	5
Heat expelled	6500 W
Air Volume	2 m ³ /h

CAPABILITIES

GN grids	[]
GN guides step	68 mm

CAPABILITIES

EN Grids	[]
Step guides EN	17.5 mm
IC grids	[]
Step IC guides	17.5 mm
5Lt tanks 360x165x120h mm	21
5Lt tanks 360x250x80h mm	14
Carapine 7Lt Ø200x250h	12

SUPPLY


Power supply	380-415 V 3N~ 50 Hz
FLI - Max cold power	4737 W
FLA - Max cold absorption	7.72 A
Power cable	5G 2,5 mm ²
Power plug	Plug not provided

PERFORMANCE


Blast chilling capacity (+65°C -> +10°C) EN ISO22042	45 kg [99.23lb]
Freezing capacity (+65°C -> -18°C) EN ISO22042	35 kg [77.17lb]
Energy consumption per blast cycle (+65°C -> +10°C) UNI EN ISO22042	0.1 kW/kg
Energy consumption per freezing cycle (+65°C -> +10°C) UNI EN ISO22042	0.33 kW/kg
Blast-down time (+65°C -> +10°C) UNI EN ISO22042	120 min
Freezing time (+65°C -> -18°C) UNI EN ISO22042	270 min

DIMENSIONS



Vista Frontale
Frontal side



Vista Laterale
Lateral side



Vista Superiore
Top View



Display con tasti capacitivi
Display with capacitive keys

Cavo alimentazione elettrica
Power supply cable

Impianto frigo
Refrigeration system

Scatola elettrica
Electric box

Tubo scarico acqua
Drain pipe