




PERFORMANCE

PRODUCT YIELDS +90°C/+3°C	85 kg
PRODUCT YIELDS +90°C/-18°C	70 kg
TEMPERATURE RANGE	-40°C / +5°C
CAPABILITIES	15 pans
STEP GASTRONOMY GUIDES	68 mm
STEP PASTRY GUIDES	17.5 mm
STEP ICE CREAM GUIDES	17.5 mm
ICE CREAM TRAYS 165x360x120h mm	21
ICE CREAM TRAYS 250x360x120h mm	14
ICE CREAM TRAYS 250x360x120h mm	12

CHECK



FEATURES

- Next-generation electronic fans (5 different speeds)
- Insulation in high density expanded polyurethane (approximately 42 kg/m3), HCFC free - Thickness 60 mm
- Maximum flexibility to optimize and customize the daily work process
- Total inspectability of the room for maximum hygiene
- Air condensation
- 4-point heated heart core included
- HACCP usb port included
- Refrigerant fluid R290
- Evaporating coil in copper-aluminum, cataphoresis painted with non-toxic epoxy resin
- Condensate collection tray
- 7" high definition touch display on the door, easy to use
-
- USB port for cycle download, firmware upgrade, recipe upload/download etc.

OPTIONAL

- 4.0 bi-directional connectivity and Wi-Fi
- Ozone sanitization
- Wheel kit

Water condensing unit

STANDARD EQUIPMENT

AISI 304 stainless steel supports for GN1/1 or 600x400 trays

OPTIONAL EQUIPMENT

Internal structure with variable pitch featuring 15 pairs of removable "L" guides in AISI 304 stainless steel, positionable to fit every 17.5 mm

Internal structure with variable pitch featuring 15 pairs of removable anti-tipping "C" guides in AISI 304 stainless steel, positionable to fit every 17.5 mm

DIMENSIONS

Width	790 mm [31.1 in]
Depth	1030 mm [40.55 in]
Height	1950 mm [76.77 in]
Weight	190 kg [418.95 lb]
Foot height	145-205 mm [5.71-8.07 in]
Door light width 1	670 mm [26.38 in]
Door light height 1	1130 mm [44.49 in]
Door depth open 90°	1740 mm [68.5 in]
Internal depth	410 mm [16.14 in]
Packaging width	850 mm [33.46 in]
Packing depth	1090 mm [42.91 in]
Packaging height	2095 mm [82.48 in]
Packing weight	196 kg [432.18 lb]
Packing volume	1.94 m ³ [512.76 glus]

TECHNICAL DATA

Temperature range	-40°C / +5°C
Insulation thickness	60 mm [2.36in]
Number of rooms	1
Door type	Blind
Number of doors	1
Condensation type	Air
Plant type	Motor on board
Plant type	Ventilated
Compressor type	Hermetic
Refrigerant gas	R290
GWP refrigerant gas	3
Refrigerant gas quantity g	3 x 150 g [3 x 5.91oz]
Cooling power ASHRAE lbp	4620 W [15754.2btu/h]
Sound power	<70 dbA
Expansion valve type	Mechanics
Defrost type	Open door
Defrost water evaporation	Exhaust pipe
Interior lighting	Not present
Outdoor lighting	Not present
Cooling power	10050 W
Climatic class	5
Heat expelled	9500 W
Air Volume	3 m ³ /h

CAPABILITIES

GN grids	[]
GN guides step	68 mm
EN Grids	[]
Step guides EN	17.5 mm
IC grids	[]
Step IC guides	17.5 mm
5Lt tanks 360x165x120h mm	21
5Lt tanks 360x250x80h mm	14
Carapine 7Lt Ø200x250h	12

SUPPLY

Power supply	380-415 V 3N~ 50 Hz
FLI - Max cold power	4600 W
FLA - Max cold absorption	8 A
Max hot power	700 W
Max hot absorption	3.0434782608696 A
Power cable	5G 2,5 mm ²
Power plug	Plug not provided

PERFORMANCE

Blast chilling capacity (+65°C -> +10°C) EN ISO22042	75 kg [165.38lb]
Freezing capacity (+65°C -> -18°C) EN ISO22042	55 kg [121.28lb]
Energy consumption per blast cycle (+65°C -> +10°C) UNI EN ISO22042	0.07 kW/kg
Energy consumption per freezing cycle (+65°C -> +10°C) UNI EN ISO22042	0.27 kW/kg
Blast-down time (+65°C -> +10°C) UNI EN ISO22042	120 min
Freezing time (+65°C -> -18°C) UNI EN ISO22042	270 min