



#### PERFORMANCE

TEMPERATURE RANGE	-25°C / -15°C
GASTRONOMY SET-UP	Rilsan grills GN2/1
GASTRONOMY GRILLS	3
STEP GASTRONOMY GUIDES	55 mm

#### CHECK



#### FEATURES

- AISI 304 stainless steel construction with scotch-brite exterior finish
- Monocoque structure with increased loading mouth height and large loading volume
- Foamed engine compartment sides for improved robustness and soundproofing
- Interior with rounded edges for easy cleaning
- Self-closing and reversible doors (with kit)
- Door frame with easily replaceable heating element
- Magnetic door gasket, replaceable without tools
- Height-adjustable AISI 304 stainless steel feet
- Possibility of inserting up to 36 shelves with 55 mm pitch
- Refrigerant gas R290
- Ventilated refrigeration system
- LCD display with capacitive touch controls

#### STANDARD EQUIPMENT

3 rilsan-type grills GN2/1

## DIMENSIONS

Width	700 mm [27.56 in]
Depth	830 mm [32.68 in]
Height	1930 mm [75.98 in]
Weight	117 kg [257.99 lb]
Foot height	105-170 mm [4.13-6.69 in]
Door light width 1	550 mm [21.65 in]
Door light height 1	1325 mm [52.17 in]
Packaging width	740 mm [29.13 in]
Packing depth	890 mm [35.04 in]
Packaging height	2200 mm [86.61 in]
Packing weight	139 kg [306.5 lb]
Packing volume	1.44 m <sup>3</sup> [382.76 glus]

## TECHNICAL DATA

Temperature range	-25°C / -15°C
Insulation thickness	83 mm [3.27in]
Number of rooms	1
Door type	Blind
Number of doors	1
Condensation type	Air
Plant type	Motor on board
Plant type	Ventilated
Compressor type	Hermetic
Refrigerant gas	R290
GWP refrigerant gas	3
Sound power	< 70 dbA
Defrost type	Electric
Defrost water evaporation	Automatic
Interior lighting	Not present
Outdoor lighting	Led
Climate class	5
Energy class	C

## CAPABILITIES

GN Setup	Rilsan grills GN2/1
GN grids	[ "3" ]
GN guides step	55 mm

## SECONDARY ELECTRICAL DATA

Power cable	3G 1,5 mm <sup>2</sup>
Power plug	CE-Schuko

