



PERFORMANCE

TEMPERATURE RANGE	-2°C / +8°C
CAPABILITIES	677 l
GASTRONOMY SET-UP	"L" guide pairs
STEP GASTRONOMY GUIDES	34 mm

CHECK



FEATURES

- AISI 304 stainless steel construction with scotch-brite exterior finish
- Monocoque structure with increased loading mouth height and large loading volume
- Foamed engine compartment sides for improved robustness and soundproofing
- Interior with rounded edges for easy cleaning
- Self-closing and reversible doors (with kit)
- Door frame with easily replaceable heating element
- Magnetic door gasket, replaceable without tools
- Height-adjustable AISI 304 stainless steel feet
- Possibility of inserting up to 36 shelves with 35 mm pitch
- Refrigerant gas R290
- Static refrigeration system
- Easy-to-use, high-definition 4.3" full touch display
- Native internet connection / cloud / remote diagnostics and control
- Integrated network card with Ethernet output included (wifi optional)
- Possibility of storing recipes

DIMENSIONS	
Width	790 mm [31.1 in]
Depth	1030 mm [40.55 in]
Height	2110 mm [83.07 in]
Weight	160 kg [352.8 lb]
Foot height	97-159 mm [3.82-6.26 in]
Door light width 1	610 mm [24.02 in]
Door light height 1	1510 mm [59.45 in]
Inner depth	815 mm [32.09 in]
Packaging width	845 mm [33.27 in]
Packing depth	1095 mm [43.11 in]
Packaging height	2200 mm [86.61 in]
Packing weight	195 kg [429.98 lb]
Packing volume	2.03 m ³ [537.75 glus]

TECHNICAL DATA	
Temperature range	-2°C / +8°C
Insulation thickness	85 mm [3.35in]
Number of rooms	1
Door type	Blind
Number of doors	1
Condensation type	Air
Plant type	Motor on board
Plant type	Ventilated
Compressor type	Hermetic
Refrigerant gas	R290
GWP refrigerant gas	3
Refrigerant gas quantity g	90 g [5.63oz]
Sound power	< 70 dbA
Defrost type	Hot gas
Defrost water evaporation	Automatic
Interior lighting	Not present
Outdoor lighting	Led
Climate class	5
Energy class	C

CAPABILITIES	
GN Setup	"L" guide pairs
Pair of GN guides	15
GN guides step	34 mm

SECONDARY ELECTRICAL DATA

Power cable	3G 1,5 mm ²
Power plug	CE-Schuko