




PERFORMANCE

TEMPERATURE RANGE	-3°C / +18°C
HUMIDITY RANGE	40% / 90%
PASTRY SET-UP	L" guide pairs
STEP PASTRY GUIDES	60 mm

CHECK



FEATURES

- AISI 304 stainless steel construction with scotch-brite exterior finish
- Monocoque structure with increased loading mouth height and large loading volume
- Foamed engine compartment sides for improved robustness and soundproofing
- Interior with rounded edges for easy cleaning
- Self-closing and reversible doors (with kit)
- Door frame with easily replaceable heating element
- Magnetic door gasket, replaceable without tools
- Height-adjustable AISI 304 stainless steel feet
- Possibility of inserting up to 36 shelves with 35 mm pitch
- Refrigerant gas R290
- Static refrigeration system
- Easy-to-use, high-definition 4.3" full touch display
- Native internet connection / cloud / remote diagnostics and control
- Integrated network card with Ethernet output included (wifi optional)
- Possibility of storing recipes

DIMENSIONS

Width	790 mm [31.1 in]
Depth	750 mm [29.53 in]
Height	2110 mm [83.07 in]
Weight	132 kg [291.06 lb]
Foot height	97-159 mm [3.82-6.26 in]
Door light width 1	620 mm [24.41 in]
Door light height 1	1510 mm [59.45 in]
Door depth open 90°	1480 mm [58.27 in]
Inner depth	540 mm [21.26 in]
Packaging width	845 mm [33.27 in]
Packing depth	815 mm [32.09 in]
Packaging height	2200 mm [86.61 in]
Packing weight	161 kg [355 lb]
Packing volume	1.51 m ³ [400.24 glus]

TECHNICAL DATA

Temperature range	-3°C / +18°C
Humidity range	40% / 90%
Insulation thickness	85 mm [3.35in]
Number of rooms	1
Door type	Blind
Number of doors	1
Condensation type	Air
Plant type	Motor on board
Plant type	Ventilated
Compressor type	Hermetic
Refrigerant gas	R290
GWP refrigerant gas	3
Refrigerant gas quantity g	89 g [5.56oz]
Sound power	<70 dbA
Defrost type	Hot gas
Defrost water evaporation	Automatic
Interior lighting	Not present
Outdoor lighting	Led
Cooling power	555 W [1892.55BTU/h]
Climate class	5
Energy class	C
lee	47.64
kW/24h	1.7 kW

CAPABILITIES		
EN Setup		L" guide pairs
Pair of EN guides		24
Step guides EN		60 mm
SECONDARY ELECTRICAL DATA		
Power cable		(2+1) x 1,5 mm ²
Power plug		CE-Schuko

The manufacturer reserves the right to change models and specifications without prior notice.