




PERFORMANCE

TEMPERATURE RANGE	-30°C / -15°C
ICE CREAM SETUP	"C" guide pairs
ICE CREAM CRATES	5
ICE CREAM TRAYS 165x360x120h mm	60
ICE CREAM TRAYS 250x360x120h mm	42

CHECK



FEATURES

- AISI 304 stainless steel construction with scotch-brite exterior finish
- Monocoque structure with increased loading mouth height and large loading volume
- Foamed engine compartment sides for improved robustness and soundproofing
- Interior with rounded edges for easy cleaning
- Self-closing and reversible doors (with kit)
- Door frame with easily replaceable heating element
- Magnetic door gasket, replaceable without tools
- Height-adjustable AISI 304 stainless steel feet
- Possibility of inserting up to 36 shelves with 35 mm pitch
- Refrigerant gas R290
- Static refrigeration system
- Easy-to-use, high-definition 4.3" full touch display
- Native internet connection / cloud / remote diagnostics and control
- Integrated network card with Ethernet output included (wifi optional)
- Possibility of storing recipes

DIMENSIONS

Width	790 mm [31.1 in]
Depth	915 mm [36.02 in]
Height	1980 mm [77.95 in]
Weight	171 kg [377.06 lb]
Foot height	97-159 mm [3.82-6.26 in]
Door light width 1	610 mm [24.02 in]
Door light height 1	1510 mm [59.45 in]
Inner depth	742 mm [29.21 in]
Packaging width	840 mm [33.07 in]
Packing depth	980 mm [38.58 in]
Packaging height	2200 mm [86.61 in]
Packing weight	206 kg [454.23 lb]
Packing volume	1.81 m ³ [478.42 glus]

TECHNICAL DATA

Temperature range	-30°C / -15°C
Insulation thickness	85 mm [3.35in]
Number of rooms	1
Door type	Blind
Number of doors	1
Condensation type	Air
Plant type	Motor on board
Plant type	Ventilated
Compressor type	Hermetic
Refrigerant gas	R290
GWP refrigerant gas	3
Refrigerant gas quantity g	150 g [9.38oz]
Sound power	< 70 dbA
Defrost type	Hot gas
Defrost water evaporation	Automatic
Interior lighting	Not present
Outdoor lighting	Led
Climate class	5
Energy class	D

CAPABILITIES

IC Setup	"C" guide pairs
IC guide pair	5
Stainless steel trays	5
5Lt tanks 360x165x120h mm	60
5Lt tanks 360x250x80h mm	42

SECONDARY ELECTRICAL DATA

Power cable	3G 1,5 mm ²
Power plug	CE-Schuko