




PERFORMANCE	
TEMPERATURE RANGE	-30°C / -12°C
CAPABILITIES	470 l
ICE CREAM CRATES	5
STEP ICE CREAM GUIDES	35 mm
ICE CREAM TRAYS 165x360x120h mm	32
ICE CREAM TRAYS 250x360x120h mm	18

CHECK



- FEATURES
- AISI 304 stainless steel construction with scotch-brite exterior finish
 - Monocoque structure with increased loading mouth height and large loading volume
 - Foamed engine compartment sides for improved robustness and soundproofing
 - Interior with rounded edges for easy cleaning
 - Self-closing and reversible doors (with kit)
 - Door frame with easily replaceable heating element
 - Magnetic door gasket, replaceable without tools
 - Height-adjustable AISI 304 stainless steel feet
 - Possibility of inserting up to 36 shelves with 55 mm pitch
 - Refrigerant gas R290
 - Ventilated refrigeration system
 - LCD display with capacitive touch controls

DIMENSIONS	
Width	700 mm [27.56 in]
Depth	830 mm [32.68 in]
Height	1930 mm [75.98 in]
Foot height	105-170 mm [4.13-6.69 in]
Door light width 1	550 mm [21.65 in]
Door light height 1	1325 mm [52.17 in]
Inner depth	711 mm [27.99 in]
Packaging width	740 mm [29.13 in]
Packing depth	890 mm [35.04 in]
Packaging height	2200 mm [86.61 in]
Packing weight	165 kg [363.82 lb]
Packing volume	1.44 m ³ [382.76 glus]

TECHNICAL DATA	
Temperature range	-30°C / -12°C
Insulation thickness	75 mm [2.95in]
Number of rooms	1
Door type	Blind
Number of doors	1
Condensation type	Air
Plant type	Motor on board
Plant type	Ventilated
Compressor type	Hermetic
Refrigerant gas	R290
GWP refrigerant gas	3
Refrigerant gas quantity g	126 g [7.88oz]
Sound power	< 70 dbA
Defrost type	Electric
Defrost water evaporation	Automatic
Interior lighting	Not present
Outdoor lighting	Led
Climate class	5
Energy class	F

CAPABILITIES	
IC guide pair	5
Stainless steel trays	5
Step IC guides	35 mm
5Lt tanks 360x165x120h mm	32
5Lt tanks 360x250x80h mm	18

SECONDARY ELECTRICAL DATA

Power cable	3G 1,5 mm ²
Power plug	CE-Schuko