



PERFORMANCE

TEMPERATURE RANGE	-10°C / +40°C
CAPABILITIES	1 trolley 600x800mm or 2 trolleys 600x400mm

CHECK



FEATURES

- High energy saving
- State-of-the-art electronic fans
- Energy-efficient fans
- Electronically controlled proportional humidifier

- Easy-to-use, high-definition 7" full touch display
- Bi-directional 4.0 connectivity
- USB port for recipe downloads, firmware upgrades, recipe uploads/downloads, HACCP downloads.
- Ethernet connection
- Storable recipes
- Multilingual It-en-fr-es-de-dk-cz-fi

DIMENSIONS

Width	930 mm [36.61 in]
Depth	1269 mm [49.96 in]
Height	2450 mm [96.46 in]
Door light width 1	770 mm [30.31 in]
Door light height 1	1770 mm [69.69 in]
Door depth open 90°	1973 mm [77.68 in]

TECHNICAL DATA

Temperature range	-10°C / +40°C
Door type	Blind
Condensation type	Air
Plant type	Motor on board
Plant type	Ventilated
Compressor type	Hermetic
Refrigerant gas	R452A
GWP refrigerant gas	2141
Water inlet connection	3/4 NTPf
Sound power	< 70 dbA
Defrost type	Electric

SECONDARY ELECTRICAL DATA

Power resistive loads	1000 W
Power cable	3G 1,5 mm ²
Power plug	CE-Schuko